

Preliminary Amendment

Applicant(s): HOOPMAN et al.

Serial No.: 09/520,032

Filed: 6 March 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

Page 2 of 17

In the Claims

Please cancel claims 1-16, 18, 22-24, 29-32, 88-93, and 97 as requested in the Request for Continued Prosecution Application Under Rule §1.53(d), filed concurrently herewith. The amended claims are provided below in clean form. Per 37 C.F.R. §1.121, amended claims are also shown in Appendix A with notations to indicate changes made (for convenience, all pending claims, including those added hereby, are provided in Appendix A).

62 Sub 017
17. (AMENDED) The production tool of claim 16, wherein each said pyramidal shape comprises planar surfaces which intersect to form a material-included angle at a distal end of said pyramid, wherein said material-included angle is a value from 25° to 90°.

19. (AMENDED) A production tool useful to shape an abrasive slurry into an array of three-dimensional nonidentical abrasive composites, said production tool manufactured by a method comprising:

(A) preparing a master tool, the method comprising:

13 Sub 017
(1) determining angles corresponding to facing right and left planar surfaces of adjacent three-dimensional shapes and wherein each of said angles has a value as measured between its planar surface and a plane which extends in a normal direction to said major surface and contains an edge of said planar surface in contact with said major surface, by the following substeps:

(i) selecting an angle value between, but not including, 0° and 90° to establish a first right half angle of a first right planar surface of a first right-side three-dimensional shape with a random number generating means capable of randomly selecting an angle value between, but not including, 0° and 90°;

(ii) selecting an angle value between, but not including, 0° and 90° with said random number generating means to establish a first-left-half-angle-for-a-first-left-planar-surface of a first left-side three-dimensional shape facing said first right planar surface of said first right-side three-dimensional shape;

Preliminary Amendment

Applicant(s): HOOPMAN et al.

Serial No.: 09/520,032

Filed: 6 March 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

Page 3 of 17

(iii) proceeding along a first direction extending linearly within said first imaginary plane to a second left planar surface of a second left-side three-dimensional shape located adjacent said first left-side three-dimensional shape and using said random number generating means to select a value between, but not including, 0° and 90° to establish a second left planar angle for said second left planar surface;

(iv) using said random number generating means to select a value between, but not including, 0° and 90° for a second right planar surface of a second right-side three-dimensional shape facing said second left planar surface;

(v) proceeding along said first direction to a third right-side three-dimensional shape located adjacent said second right-side three-dimensional shape;

(vi) repeating said substeps (i), (ii), (iii), (iv), and (v), in that sequence, at least once;

(2) repeating step (1) except that the angles are determined for left and right planar surfaces of adjacent three-dimensional shapes deployed in two adjacent rows in a second direction extending linearly within said first imaginary plane, wherein said first and second directions intersect;

(3) using means to determine, for a given width of said surface of said master, locations of grooves required to be cut by a cutting means to form a series of intersecting grooves defining a plurality of three-dimensional shapes having said angles calculated by steps (1) and (2); and

(4) providing a cutting means to cut grooves in said surface of said master in correspondence to said angles calculated by steps (1) and (2) and said groove locations determined by step (3) to form a series of intersecting grooves which define a plurality of three-dimensional shapes upraised from said surface, each of said shapes being defined by a distinct and discernible boundary including specific dimensions, wherein not all said three-dimensional shapes are identical; and

(B) forming a production tool using the master tool.

20. (AMENDED) The production tool of claim 14 which is a roll.

21. (AMENDED) A production tool for manufacturing an abrasive article that comprises a major surface having deployed in fixed position thereon first and second three-dimensional abrasive composites, each of said composites comprising abrasive particles dispersed in a binder and having a shape defined by a substantially distinct and discernible boundary which includes substantially specific dimensions, wherein said first abrasive composite has a shape having specific first dimensions and said second abrasive composite has a second shape having second specific dimensions, wherein each of said abrasive composites has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one composite meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first abrasive composite is different from all of the angles of intersection of said second composite, said production tool comprising a structure having a plurality of adjacent three-dimensional cavities form on a major surface thereof, wherein each three-dimensional cavity is defined by a substantially distinct and discernible boundary which includes substantially specific dimensions, wherein a first three-dimensional cavity has a first shape having specific first dimensions and a second three-dimensional cavity has a second shape having second specific dimensions, wherein each of said three-dimensional cavities has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one three-dimensional cavity meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first three-dimensional cavity is different from all angles of intersection of said second three-dimensional cavity, wherein the production tool is a coating roll.

33. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first and second plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape and the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second plurality of angles, wherein the production tool is a coating roll.

34. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, and the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second and third plurality of angles, and wherein at least one of the angles of the second plurality is different from all of the angles of the first and third plurality of angles, wherein the production tool is a coating roll.

35. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape and fourth plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second, third, and fourth plurality of angles, wherein at least one of the angles of the second plurality is different from all of the angles of the first, third, and fourth plurality of angles, and wherein at least one of the angles of the third plurality is different from all of the angles of the first, second, and fourth plurality of angles, wherein the production tool is a coating roll.

36. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 10% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is a coating roll.

37. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 30% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is a coating roll.

38. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 50% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is a coating roll.

39. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have a geometric shape, dimensions defining the cavity, and angles forming the geometric shape, wherein the angles are different in at least two of the cavities, and further wherein at least 10% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is a coating roll.

40. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, and wherein at least two adjacent cavities have at least one dimension different between the two cavities, wherein the production tool is a coating roll.

41. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defining at least a first and a second group, wherein a first group of cavities has a first shape and a second group of cavities has a second, different, shape, wherein the production tool is a coating roll.

42. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defining at least a first and a second group, wherein a first group of

cavities has a first size and a second group of cavities has a second, different, size, wherein the production tool is a coating roll.

43. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defined by substantially distinct and discernible boundaries which include substantially specific dimensions, wherein a first cavity has specific first dimensions and a second cavity has specific second dimensions, and further wherein each of said cavities has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one cavity meet at an edge to define an angle of intersection therebetween, wherein at least one angle of intersection of said first cavity is different from all the angles of intersection of said second cavity, wherein the production tool is a coating roll.

44. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first and second plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape and the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second plurality of angles, wherein the production tool is an engraved metal roll.

45. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, and the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second and third plurality of angles, and wherein at least one of the angles of the second plurality is different from all of the angles of the first and third plurality of angles, wherein the production tool is an engraved metal roll.

46. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape and first plurality of angles forming the geometric shape, the second plurality of cavities each have a second geometric shape and second plurality of angles forming the geometric shape, the third plurality of cavities each have a third geometric shape and third plurality of angles forming the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape and fourth plurality of angles forming the geometric shape, wherein at least one of the angles of the first plurality is different from all of the angles of the second, third, and fourth plurality of angles, wherein at least one of the angles of the second plurality is different from all of the angles of the first, third, and fourth plurality of angles, and wherein at least one of the angles of the third plurality is different from all of the angles of the first, second, and fourth plurality of angles, wherein the production tool is an engraved metal roll.

47. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 10% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is an engraved metal roll.

48. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 30% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is an engraved metal roll.

49. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, wherein at least 50% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is an engraved metal roll.

50. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have a geometric shape, dimensions defining the cavity, and angles forming the geometric shape, wherein the angles are different in at least two of the cavities, and further wherein at least 10% of pairs of adjacent cavities have at least one dimension different between the two cavities of the pair, wherein the production tool is an engraved metal roll.

51. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, and wherein at least two adjacent cavities have at least one dimension different between the two cavities, wherein the production tool is an engraved metal roll.

52. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defining at least a first and a second group, wherein a first group of cavities has a first shape and a second group of cavities has a second, different, shape, wherein the production tool is an engraved metal roll.

53. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defining at least a first and a second group, wherein a first group of cavities has a first size and a second group of cavities has a second, different, size, wherein the production tool is an engraved metal roll.

54. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities defined by substantially distinct and discernible boundaries which include substantially specific dimensions, wherein a first cavity has specific first dimensions and a second cavity has specific second dimensions, and further wherein each of said cavities has a boundary defined by at least four planar surfaces wherein adjacent planar surfaces of one cavity meet at an edge

Preliminary Amendment

Applicant(s): HOOPMAN et al.

Serial No.: 09/520,032

Filed: 6 March 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

Page 10 of 17

to define an angle of intersection therebetween, wherein at least one angle of intersection of said first cavity is different from all the angles of intersection of said second cavity, wherein the production tool is an engraved metal roll.

~~98. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first and second plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape and the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second plurality of base edge lengths, production tool is a coating roll.~~

99. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, and the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second and third plurality of base edge lengths, and wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first and third plurality of base edge lengths, production tool is a coating roll.

100. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape

Preliminary Amendment

Page 11 of 17

Applicant(s): HOOPMAN et al.

Serial No.: 09/520,032

Filed: 6 March 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

~~including a base and second plurality of base edge lengths forming the base of the geometric shape, the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape including a base and fourth plurality of base edge lengths forming base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second, third, and fourth plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first, third, and fourth plurality of base edge lengths, and wherein at least of the base edge lengths one of the third plurality is different from all of the base edge lengths of the first, second, and fourth plurality of base edge lengths, production tool is a coating roll.~~

101. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 10% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, production tool is a coating roll.

102. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 30% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, production tool is a coating roll.

103. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 50% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, production tool is a coating roll.

Preliminary Amendment

Applicant(s): HOOPMAN et al.

Serial No.: 09/520,032

Filed: 6 March 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

Page 12 of 17

~~104. (AMENDED) A production tool suitable for use in manufacturing an abrasive article~~
comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, and wherein at least two adjacent cavities have at least one base edge lengths different between the two cavities, production tool is a coating roll.

105. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first and second plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape and the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second plurality of base edge lengths, production tool is an engraved metal roll.

106. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, and third plurality of cavities, wherein the first plurality of cavities each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, and the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second and third plurality of base edge lengths, and wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first and third plurality of base edge lengths, production tool is an engraved metal roll.

107. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a first, second, third, and fourth plurality of cavities, wherein the first plurality of cavities

Preliminary Amendment

Applicant(s): HOOPMAN et al.

Serial No.: 09/520,032

Filed: 6 March 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

Page 13 of 17

*AS
Sub
Del*

~~each have a first geometric shape including a base and first plurality of base edge lengths forming the base of the geometric shape, the second plurality of cavities each have a second geometric shape including a base and second plurality of base edge lengths forming the base of the geometric shape, the third plurality of cavities each have a third geometric shape including a base and third plurality of base edge lengths forming the base of the geometric shape, and the fourth plurality of cavities each have a fourth geometric shape including a base and fourth plurality of base edge lengths forming base of the geometric shape, wherein at least one of the base edge lengths of the first plurality is different from all of the base edge lengths of the second, third, and fourth plurality of base edge lengths, wherein at least one of the base edge lengths of the second plurality is different from all of the base edge lengths of the first, third, and fourth plurality of base edge lengths, and wherein at least of the base edge lengths one of the third plurality is different from all of the base edge lengths of the first, second, and fourth plurality of base edge lengths, production tool is an engraved metal roll.~~

108. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 10% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, production tool is an engraved metal roll.

109. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 30% of pairs of adjacent cavities have at least one base edge length different between the two cavities of the pair, production tool is an engraved metal roll.

~~110. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, wherein at least 50% of pairs of adjacent cavities have at~~

Preliminary Amendment

Page 14 of 17

Applicant(s): HOOPMAN et al.

Serial No.: 09/520,032

Filed: 6 March 2001

For: TOOLS TO MANUFACTURE ABRASIVE ARTICLES

~~least one base edge length different between the two cavities of the pair, production tool is an engraved metal roll.~~

111. (AMENDED) A production tool suitable for use in manufacturing an abrasive article comprising a plurality of cavities, wherein the cavities each have dimensions defining the cavity, the dimensions including base edge lengths, and wherein at least two adjacent cavities have at least one base edge lengths different between the two cavities, production tool is an engraved metal roll.
